

MATERIAL SAFETY DATA SHEET – TIMBER & DECKING OIL**Hazardous according to criteria of WorkSafe Australia****PRODUCT IDENTIFICATION:**

Trade Name: Timber & Decking Oil
Chemical Name: Paint
Shipping Name: Paint
UN: 1263 Class: 3.2
Hazchem: 3 [Y] Pkg: III
EPG: 3C1

CHEMICAL COMPOSITION:

Consists of mixture of Linseed Oil, Solvent, Alkyd Resin and Driers.

PHYSICAL DATA:

Appearance: Red-brown liquid
Odour: Slight solvent odour
Boiling Point: NA
Vapour Pressure: NA
Specific Gravity: approx 0.90 (at 24 deg C)
Per cent Volatiles by Volume: Approx 40%
Solubility in Water: Insoluble

FIRE & EXPLOSION DATA:

Flash Point: 39.5 deg C
Flammability Limits in air (% by vol): NA Upper: NA
Extinguishing Media: Foam water spray (fog) or carbon dioxide. Avoid dry powder extinguishers.
Special Fire Fighting Procedures: Use foam or carbon dioxide. Minimize breathing fumes by use of breathing equipment.
Unusual Fire & Explosion Hazards: Rags used for cleaning or wiping Timber & Decking Oil are susceptible to spontaneous combustion especial in direct sunlight. Wash rags immediately after use or dispose of by burning.

REACTIVITY DATA:

Not reactive. Do not store near oxidizing agents which may cause product to gel. Avoid finely divided powders.

SPECIAL PROTECTION INFORMATION:

Ventilation: NA
Respiratory Protection: NA
Protective Clothing: NA
Eye Protection: NA
Skin Protection: NA

HEALTH HAZARD DATA:

Threshold limit value: NA
Occupational exposure level: NA
Acute Toxicity: NA
Chronic Affects: NA

FIRST AID TREATMENT:

Swallowed: DO NOT induce vomiting. Give water or milk to drink. Obtain medical attention.

Skin or Eye Contact: Flush eyes with water. Wash skin with soap and water.

Inhalation: NA

SAFE HANDLING INFORMATION:

Storage and Transport: Store in a cool area.

Spills and Disposal: If spilt, prevent runoff to drains & water courses. Inform EPA if spill is substantial. For waste disposal absorb or contain spill with sand or earth; do not use sawdust. Seal absorbed material in labelled drums and consult local waste disposal authority.

Fire/Explosion Hazard: Flammable.

PRODUCT INFORMATION:

Timber & Decking Oil is the ideal product for protection of all timbers that are exposed to weather. It highlights the grain and natural beauty of timber with minimum maintenance, will protect for decades. It is easy to apply and very low in cost. Timber & Decking Oil is also suitable for sealing mudbrick houses and sand-blasted brick work. In fact it can be used as a sealer for any surface that it can soak into. Timber & Decking Oil can also be used for a variety of indoor applications. It is ideal for sealing chipboard shelves. It can be used as a finish on all raw timber, e.g. bookshelves, tables, chairs, exposed beams, pine ceiling, ect. If a surface needs additional protecting, for example a table top, you can paint over the Timber & Decking Oil with a polyester or polyurethane finish. If colour is required, normal paint tints can be added to Timber & Decking Oil to give the desired shade.

DIRECTIONS FOR USE:

1. Apply one coat and brush in well. This coat should dry within one hour; however it is best to wait 24 hours before applying a second coat. For hard, dense timbers it may be necessary to thin the initial coat with Mineral Turps. This will allow deeper penetration into the timber.
2. Apply a light second coat again brushing in well. If the timber surface is very smooth and excess product remains on the surface after 30 minutes, wipe the excess off with a clean rag. Dispose of the rag immediately (see above) as most drying oils can self-combust especially if left in direct sunlight.
3. Clean up with Mineral Turps or Sceneys Ezyclean.

DISCLAIMER: The data provided here is based on current knowledge and experience. The purpose for this Safety Data Sheet is to describe the product in terms of its safety requirements. The data does not signify any warranty with regard to the properties or end use or handling of the product. All information is provided in good faith but without guarantee and without acceptance of responsibility of accuracy.

Prepared by Dr Greg Sceney 01/03/2013

Supplier: Sceneys Pty Ltd
17 Third Ave
Sunshine Vic 3020

Ph: (03)9311 7477
Fax: (03)9312 6911
www.sceneys.com.au