

MATERIAL SAFETY DATA SHEET – FENCE BLACK**Hazardous according to criteria of WorkSafe Australia****PRODUCT IDENTIFICATION:**

Trade Name: Fence Black
Chemical Name: Paint
Shipping Name: Paint
UN: 1263 Class: 3
Hazchem: 3 [Y] Pkg: III
EPG: 3C1

CHEMICAL COMPOSITION:

Consists of mixture of paint related minerals.

PHYSICAL DATA:

Appearance: Black liquid
Odour: Slight solvent odour
Boiling Point: >149 deg C
Vapour Pressure: (mm of Hg at 25C): >25.0
Specific Gravity: 0.95 (at 24 deg C)
Flash Point: 39.5 deg C (IP 36/ASTM D-92)
Flammability Limits: LEL 0.8% UEL 6.0%

HEALTH HAZARD INFORMATION:

HEALTH EFFECTS: Due to presence of hydrocarbon solvent, repeated skin contact may cause slight skin irritation.

ACUTE:

Swallowed: Practically non-toxic (LD50: >400mg/kg)

Eye: Practically non-irritating

Skin: Practically non-irritating

Inhaled: Practically non-toxic

FIRST AID:

Swallowed: DO NOT induce vomiting. Give 1 to 2 glasses of water. Obtain medical attention or call ambulance.

Eye: Flush thoroughly with water for at least 15 minutes. Obtain medical attention or call an ambulance if irritation persists.

Skin: Wipe skin with clean cloth then cleanse the contact area with soap and water as soon as practicable. Remove contaminated clothing and launder before reuse.

PRECAUTIONS FOR USE:

Use in well ventilated area.

Personal Protection: Normal industrial eye protection practices should be employed.

SAFE HANDLING INFORMATION:

Storage and Transport: Store in a cool area.

Spills and Disposal: If spilt, prevent runoff to drains & water courses. Inform EPA if spill is substantial. For waste disposal; absorb or contain spill with sand or earth; do not use sawdust. Seal absorbed material in labelled drums and consult local waste disposal authority.

Fire/Explosion Hazard: Flammable.

SPECIAL FIRE FIGHTING PROCEDURES:

Use foam or carbon dioxide. Minimize breathing fumes by use of breathing equipment. For fires in enclosed areas fire fighters must use self-contained breathing apparatus. Prevent runoff from fire control from entering waterways, sewers or drinking water supply.

Unusual Fire and Explosion Hazards:

Rags used for wiping or cleaning Fence Black off surfaces are susceptible to spontaneous combustion especially in direct sunlight. Wash rags immediately after use in soapy water.

OTHER INFORMATION:

Conditions to Avoid: Heat, sparks, flame and build up of static electricity.

Incompatibility (Materials to Avoid): Strong oxidisers.

Hazardous Decomposition Products: Carbon monoxide.

Hazardous Polymerisation: Will not occur.

FIRE & EXPLOSIVE DATA”

Flash Point: 39.5 deg C

Flammable Limits in air (% by vol): LEL 0.8% UEL: 6.0%

PRODUCT INFORMATION:

Fence Black is an oil-based paint that soaks deep into the timber. Consequently it stops rotting, cracking and drying. It gives an attractive Matt Black finish to the timber when dry. It is ideal for protection of fencing and all outdoor timber.

DIRECTIONS FOR USE:

1. Apply one coat and brush in well. This coat should dry within one hour; however it is best to wait 24 hours before applying a second coat. For hard, dense timbers it may be necessary to thin the initial coat with Mineral Turps. This will allow deeper penetration into the timber.
2. Apply a light second coat again brushing in well.
3. Clean up with Mineral Turps or Sceneys Ezyclean.

DISCLAIMER: The data provided here is based on current knowledge and experience. The purpose for this Safety Data Sheet is to describe the product in terms of its safety requirements. The data does not signify any warranty with regard to the properties or end use or handling of the product. All information is provided in good faith but without guarantee and without acceptance of responsibility of accuracy.

Prepared by Dr Greg Sceney 15/01/2018

Supplier: Sceneys Pty Ltd
17 Third Ave
Sunshine Vic 3020

Ph: (03)9311 7477
Fax: (03)9312 6911
www.sceneys.com.au