

## Hazardous Substance, Dangerous Goods

### 1. IDENTIFICATION

**Product name:** Sceney's Old Fashioned Weatherproof Oil

**Recommended use:** Sceney's Old Fashioned Weatherproof Oil is an ideal product for protection of all timbers that are exposed to weather. It highlights the grain and natural beauty of timber with minimum maintenance and will protect for decades. Weatherproof Oil is also suitable for sealing mudbrick houses and sand-blasted brick work. Weatherproof Oil can also be used for a variety of indoor applications as a finish on all raw timber, e.g. bookshelves, tables, chairs, exposed beams, pine ceilings, ect.

**Supplier:** Sceney's  
**ABN:** 33 006 721 213  
**Street Address:** 17 Third Ave  
Sunshine VIC 3020  
Australia  
**Telephone:** (03) 9311 7477 (Mon-Fri, 9am-4pm, AEST)  
**Facsimile:** (03) 9312 6911

### 2. HAZARD IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.

#### Signal Word

Danger

#### Hazard Classifications

Flammable Liquid – Category 3.2

Aspiration Hazard – Category 1

Skin Corrosion/Irritation – Category 2

Specific Target Organ Toxicity (Single Exposure) – Category 3 Narcotic Effects

Chronic Hazard to the Aquatic Environment – Category 2

#### Hazard Statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

#### Prevention Precautionary Statements

P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

---

**Product Name: Sceney's Old Fashioned Weatherproof Oil**

# Safety Data Sheet

- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust, fume, gas, mist, vapours or spray.
- P264 Wash hands, face and all exposed skin thoroughly after handling.
- P271 Use only outdoors or in well-ventilated areas.
- P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

## Response Precautionary Statements

- P101 If medical advice is needed, have product container or label at hand.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
- P331 Do NOT induce vomiting.
- P332+P313 if skin irritation occurs: Get medical advice/attention.
- P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam for extinction.

## Storage Precautionary Statements

- P403+P235 Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- P405 Store locked up.

**Poison Schedule:** S5. Caution

## DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of dangerous Goods on Land".

**Dangerous Goods Class:** 3

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Ingredients

| Name                           | CAS | Proportion        |
|--------------------------------|-----|-------------------|
| Soya Bean Modified Alkyd Resin |     | 15 – 20 % Approx. |
| Hydrocarbon Solvents           |     | 30 – 50 % Approx. |
| Natural Drying Oils            |     | 30 – 50 % Approx. |
| Other ingredients              |     | 5 – 10 % Approx.  |

### 4. FIRST AID MEASURES

---

**Product Name: Sceneys Old Fashioned Weatherproof Oil**

# Safety Data Sheet



If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove from exposure – avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin contact:** If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor, or for 15 minutes and transport to Doctor or Hospital.

**Eye contact:** If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Immediately rinse mouth with water. If swallowed, do not induce vomiting. Give water or milk to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

**Notes to physician:** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Hazchem code:** 3Y

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical distance to source of ignition should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment, etc.) must be eliminated both in and near the work area. Do NOT smoke.

**Firefighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILLS:** Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag of paper towel). Collect and seal in properly labelled containers or drums for disposal.

---

**Product Name:** Sceney's Old Fashioned Weatherproof Oil

**Issued:** 27 May 2019

**Page 3 of 8**

**LARGE SPILLS:** If safe to do so shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand and other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops or waterways has occurred advise local emergency services.

**Dangerous Goods – Initial Emergency Response No:** 14

## 7. HANDLING AND STORAGE

**Handling:** Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, well ventilated place out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Occupational Exposure Limit Values:** No exposure standards have been.

**Biological Limit Values:** No biological limits allocated.

**Appropriate Engineering Controls:** If using inside make sure the area is well ventilated.

**Respiratory Protection:** Not necessary in well ventilated areas.

**Eye Protection:** Not necessary with normal painting.

**Hand Protection:** Not necessary with normal painting.

**Body Protection:** Not necessary with normal painting.

**Hygiene Measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking.

## 9. PHYSICAL CHEMICAL PROPERTIES

|   |                    |
|---|--------------------|
| <b>Form:</b>                            | Liquid             |
| <b>Colour:</b>                          | Amber              |
| <b>Odour:</b>                           | Hydrocarbon        |
| <b>Solubility:</b>                      | Insoluble in water |
| <b>Specific Gravity (20°C):</b>         | N Av               |
| <b>Relative Vapour Density (air=1):</b> | >1                 |
| <b>Vapour Pressure (20°C):</b>          | N Av               |
| <b>Flash Point (°C):</b>                | 36.5               |
| <b>Flammability Limits (%):</b>         | 0.5 – 8.0          |

---

**Product Name: Sceneys Old Fashioned Weatherproof Oil**

## Safety Data Sheet

|                                       |          |
|---------------------------------------|----------|
| <b>Autoignition Temperature (°C):</b> | N Av     |
| <b>Melting Point/Range (°C):</b>      | N Av     |
| <b>Boiling Point/Range (°C):</b>      | 150 -193 |
| <b>pH:</b>                            | N App    |
| <b>Viscosity:</b>                     | N Av     |

(Typical values only – consult specification sheet)

N Av = Not available, N App = Not applicable

### 10. STABILITY AND REACTIVITY

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

**Hazardous reactions:** No known hazardous reactions.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if this product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and exposure occurs are:

#### Acute effects

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Skin contact:** In normal use contact with skin will not cause irritation.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the intestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

**Eye contact:** May be an eye irritant.

#### Acute toxicity

**Inhalation:** This material has been classified as non-hazardous.

**Ingestion:** This material has been classified as non-hazardous.

**Sensitisation:** Inhalation: This material has been classified as not a respiratory sensitiser. Skin: This material has been classified as not a skin sensitiser.

---

**Product Name: Sceney's Old Fashioned Weatherproof Oil**

**Aspiration hazard:** This material has been classified as Aspiration Hazard – Category 1.

**Specific target organ toxicity (single exposure):** This material has been classified as Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

## Chronic Toxicity

**Mutagenicity:** This material has been classified as non-hazardous.

**Carcinogenicity:** This material has been classified as non-hazardous.

**Reproductive toxicity (including via lactation):** This material has been classified as non-hazardous.

**Specific target organ toxicity (repeat exposure):** This material has been classified as non-hazardous.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100mg/L

**Long-term aquatic hazard:** This material has been classified as Category 2 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, acute toxicity estimate (based on ingredients): 1 – 10 mg/L, where the substance is not rapidly degradable and/or  $BCF \geq 500$  and/or  $\log K_{ow} \geq 4$ .

**Ecotoxicity:** No information available.

**Persistence and degradability:** No information available.

**Bio accumulative potential:** No information available.

**Mobility:** No information available.

## 13. Disposal Considerations

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protective equipment is used, see “Section 8. Exposure Controls and Personal Protection” of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with the local, regional, national and international Regulations.

## 14. TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the “Australian Code for the Transport of Dangerous Goods by Road and Rail” and the “New Zealand NZS5433: Transport of Dangerous Goods on Land”.

---

**Product Name: Sceney's Old Fashioned Weatherproof Oil**

# Safety Data Sheet



**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III  
**Hazchem Code:** 3Y  
**Emergency Response Guide No:** 14

**Proper shipping name:** PAINT

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1). if both re in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1)organic peroxides (Class 5.2), toxic substances (Class 6.31), infectious substances (class 6.2) or radioactive substances (Class 7). Exemptions may apply.

## MARINE TRANSPPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III

**Proper shipping name:** PAINT

## AIR TRANSPPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

**UN No:** 1263  
**Dangerous Goods Class:** 3  
**Packing Group:** III

**Proper shipping name:** PAINT

## 15. REGULATORY INFORMATION

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons SUSMP).

**Poisons Schedule** S5

---

**Product Name:** Sceneys Old Fashioned Weatherproof Oil

## 16. OTHER INFORMATION

### References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road and Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe Work Australia.

American Conference of Industrial Hygienists (ACGIH)

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the manufacture/supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact the provider of this SDS.